

HALOSTAR OVEN

Low-voltage halogen lamps with pin base for oven lighting



Areas of application

- Baking ovens

Product benefits

- Two to three times the luminous efficiency of conventional oven lighting
- Optimum halogen content for high temperatures
- Tempered pins for reliable contact at high temperatures
- Suitable for pyrolysis (permissible ambient temperature 450 °C)
- Contains no mercury



Product family datasheet

Technical data

	Electrical data				Photometrical data Light technica l data			Dimensions & weight			
Product description	Nominal wattage	Nominal voltage	Rated wattage	Power factor λ	Nominal luminous flux	Color temper- ature	Color render- ing index Ra	Starting time	Diameter	Overall length	Light center length (LCL)
HALOSTAR OVEN 10 W 12 V G4 ¹⁾	10.00 W	12.0 V	10.00 W	1.00	140 lm	2800 K	100	0.0 s	10.0 mm	31.0 mm	21.5 mm
HALOSTAR OVEN 20 W 12 V G4 ¹⁾	20.00 W	12.0 V	20.00 W	1.00	320 lm	2800 K	100	0.0 s	10.0 mm	31.0 mm	22.0 mm

	Lifespan				Additional product data			Capabilities	Certificates & standards	
Product description	Nominal lamp life time	Rated lamp life time	Number of switching cycles	Lumen main. fact. at end of nom. life time	Base (standard designation)	Lamp mercury content	Mercury- free	Burning position	Dimmable	Energy efficiency class
HALOSTAR OVEN 10 W 12 V G4 ¹⁾	2000 h ²⁾	2000 h	50000 ³⁾	0.80	G4	0.0 mg	Yes	Any	Yes	С
HALOSTAR OVEN 20 W 12 V G4 ¹⁾	2000 h ²⁾	2000 h	50000 3)	0.80	G4	0.0 mg	Yes	Any	Yes	С


		Country specific categorizations
Product description	Energy	ILCOS
	consumption	
HALOSTAR OVEN 10 W 12 V G4 ¹⁾	11 kWh/1000h	HSGT/C/UB-10-12-G4-10/21,5
HALOSTAR OVEN 20 W 12 V G4 ¹⁾	22 kWh/1000h	HSGST/C/UB-20-12-G4-10/22

¹⁾ Heat-resistant up to 300°C/Lamp suitable for oven with high temperature self cleaning (Lamps must be switched off! Max. ambient temperature 450 °C)/For use in shielded luminaires only

 $^{^{2)}}$ Average lifespan at room temperature; higher temperature can reduce the lifespan

³⁾ At 1 min on / 3 min off

Product family datasheet



HALOSTAR OVEN 10 W 12 V G4, HALOSTAR OVEN 20 W 12 V G4

Application advice

For more detailed application information and graphics please see product datasheet.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300308081	HALOSTAR OVEN 10 W 12 V G4	Shipping carton box 40	144 mm x 107 mm x 121 mm	1.86 dm³	196.00 g
4050300308050	HALOSTAR OVEN 20 W 12 V G4	Shipping carton box 40	144 mm x 107 mm x 121 mm	1.86 dm³	178.60 g

Product family datasheet

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight	
--------------	---------------------	------------------------------	--------------------------------------	--------	--------------	--

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.